

County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 17,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

17149

CHAINS										
	<p style="text-align: center;">Set a steel fence post alongside aluminum rod.</p> <p>Continue over nearly level land.</p>									
83.22	<p>The 1/4 sec. cor. of secs. 8 and 17.</p>									
	<p>From the 1/4 sec. cor. of secs. 16 and 17,</p> <p>S. 88° 57' W., on a weighted mean bearing on the E. and W. center line of sec. 17.</p> <p>Ascend 50 ft. over SE. slope, through moderate timber and dense undergrowth.</p>									
7.00	<p>Top of ascent slopes S.; desc. 80 ft. over broken W. slope.</p>									
20.15	<p>Point for the center E 1/16 sec. cor. of sec. 17.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr> <td style="padding: 0 10px;">C</td> <td style="border-left: 1px solid black; padding: 0 5px; text-align: center;"> $\frac{E\ 1/16}{S\ 17}$ </td> <td style="padding: 0 10px;">C</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px; text-align: center;">1982</td> <td></td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears S. 9° E., 55 1/2 lks. dist., mkd. CE 1/16 S17 BT.</p> <p style="margin-left: 40px;">A hemlock, 12 ins. diam., bears N. 87° W., 18 lks. dist., mkd. CE 1/16 S17 BT.</p> <p>Descend 120 ft. over W. slope.</p>	C	$\frac{E\ 1/16}{S\ 17}$	C		1982				
C	$\frac{E\ 1/16}{S\ 17}$	C								
	1982									
22.35	<p>U.S. Highway No. 101, asphalt surface, 85 lks. wide, bears N. 20° W. and S. 20° E.</p>									
22.775	<p>Intersection of U.S. Highway No. 101 and entrance to Dunes Overlook Park, asphalt surface, 45 lks. wide, bears W.</p>									
29.80	<p>Asphalt surfaced road, 40 lks. wide, bears N. 20° E. and S. 20° W.</p>									
32.00	<p>Gravelled foot path, 6 lks. wide, bears N. and S.</p>									
32.90	<p>Gravelled foot path, 6 lks. wide, bears N. and S.</p>									
33.70	<p>Leave timber and undergrowth, edge bears N. and S.; enter rolling sand dunes.</p>									
40.30	<p>The center 1/4 sec. cor. of sec. 17,</p> <p>Continue over nearly level open rolling sand dunes.</p>									
75.10	<p>Intersect the adjusted meanders of the Pacific Ocean; point for the special meander cor. on the E. and W. center line of sec. 17.</p> <p>Set an aluminum rod, 4 ft. long, 5/8 in. diam., 3 1/2 ft. in the ground, in concrete, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr> <td style="padding: 0 10px;">SMC</td> <td style="border-left: 1px solid black; padding: 0 5px; text-align: center;">S</td> <td style="padding: 0 10px;">C</td> </tr> <tr> <td style="padding: 0 10px;">C</td> <td style="border-left: 1px solid black; padding: 0 5px; text-align: center;">17</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px; text-align: center;">1982</td> <td></td> </tr> </table> </div>	SMC	S	C	C	17			1982	
SMC	S	C								
C	17									
	1982									