

# County Surveyor's Record, Douglas County, Oregon

17154

Subdivision of Sec. 20,  
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
24.265	<p>Point selected for a witness point on the N. and S. center line of the NE 1/4 of sec. 20, at intersection with the 60 ft. westerly right-of-way of U.S. Highway No. 101.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p style="margin: 0;">WP E S   20 E 1982</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 29° E., 31 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 86 3/4° W., 38 lks. dist., mkd. X BT.</p> <p>Ascend 25 ft. over E. slope.</p>
25.26	<p>Point for Angle Point No. 2 of Parcel G, hereinafter described.</p> <p>Ascend 50 ft. over E. slope.</p>
28.21	<p>Top of ascend, slopes NE.; desc. 85 ft. over N. slope.</p>
32.97	<p>Point for Angle Point No. 1 of Parcel G, hereinafter described.</p> <p>Descend 50 ft. over N. slope.</p>
34.30	<p>S. edge of lake, bears N. 85° W. and S. 85° E.; thence across lake.</p>
40.115	<p>True point for the E 1/16 sec. cor. of secs. 17 and 20.</p>
	<p>From the N 1/16 sec. cor. of secs. 20 and 21.</p> <p>S. 88° 12' W., on the E. and W. center line of the NE 1/4 of sec. 20.</p> <p>Descend 85 ft. over SW. slope, through moderate timber and dense undergrowth.</p>
4.05	<p>Bottom of descent, slopes N. 15° W.; asc. 75 ft. over E. slope.</p>
6.15	<p>Gravelled road, 25 lks. wide, bears N. 30° W. and S. 30° E.</p>
8.60	<p>Top of ascent, slopes N.; desc. 70 ft. over NW. slope.</p>
20.365	<p>The NE 1/16 sec. cor. of sec. 20.</p> <p>Descend 35 ft. over NW. slope.</p>
23.55	<p>U.S. Highway No. 101, asphalt surface, 50 lks. wide, bears NE. and SW. in curve; also bottom of descent in road cut; asc. 10 ft. along broken S. slope, changing to SW. slope.</p>