

# County Surveyor's Record, Douglas County, Oregon

17155

Subdivision of Sec. 20,  
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS 40.71	<p>The center N 1/16 sec. cor. of sec. 20.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 20 and 29.</p> <p>N. 0° 20' W., on the N. and S. center line of the SW 1/4 of sec. 20.</p> <p>Descend slightly over rolling sand dunes, through scattering timber and dense undergrowth.</p>
21.49	<p>Intersect the adjusted meanders of the right bank of Tahkenitch Creek; no monument set.</p> <p>Descend 20 ft. over rolling sand dunes.</p>
24.15	<p>Tahkenitch Creek, 100 lks. wide, course W.; asc. 85 ft. over rolling sand dunes.</p>
30.35	<p>Top of ascent, slopes W.; desc. 70 ft. over open rolling sand dunes.</p>
39.99	<p>The center W 1/16 sec. cor. of sec. 20.</p> <hr/> <p>N. 0° 19' W., on the N. and S. center line of the NW 1/4 of sec. 20.</p> <p>Over nearly level open rolling sand dunes.</p>
20.02	<p>Point for the NW 1/16 sec. cor. of sec. 20, at intersection with the E. and W. center line of the NW 1/4.</p> <p>Set an aluminum rod, 4 ft. long, 5/8 in. diam., 3 1/2 ft. in the ground, in concrete, with aluminum cap mkd.</p> <p style="text-align: center;">NW 1/16 S 20 1982</p> <p>No suitable trees available.</p> <p>Set a steel fence post alongside aluminum rod.</p> <p>Continue over nearly level open sand dunes.</p>
40.04	<p>The W 1/16 sec. cor. of secs. 17 and 20.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 20.</p> <p>S. 88° 09' W., on the E. and W. center line of the NW 1/4 of sec. 20.</p> <p>Descend 155 ft. over W. slope, through scattering timber and dense undergrowth.</p>
2.00	<p>Enter open rolling sand dunes, edge bears N. and S.</p>
20.31	<p>The NW 1/16 sec. cor. of sec. 20.</p> <p>Continue over nearly level open rolling sand dunes.</p>
40.62	<p>The N 1/16 sec. cor. of secs. 19 and 20.</p>