

# County Surveyor's Record, Douglas County, Oregon

17158

Subdivision of Sec. 29,  
T. 20 S., R. 12 W., Willamette Meridian, Oregon

| CHAINS |   |
|--------|---|
|        | <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="display: flex; align-items: center; justify-content: center;"> <div style="margin-right: 20px; text-align: right;"> <p><i>File Renewal<br/>Sec. 29 12 W / 124 - 3<br/>1990</i></p> </div> <div style="text-align: center;"> </div> </div> <p style="text-align: center;">1982</p> <p>from which</p> <p style="margin-left: 40px;">A fir, 5 ins. diam., bears N. 82 1/4° W., 45 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">No other suitable trees available.</p> <p style="margin-left: 40px;">Set a steel fence post alongside aluminum post.</p> |
| 52.85  | <p>W. edge of Tahkenitch Lake, bears N. and S. 15° E.; thence across swampy area of Tahkenitch Lake.</p>  |
| 58.15  | <p>Intersect the adjusted meanders of Tahkenitch Lake; true point for the special meander cor. on the E. and W. center line of sec. 29. Point is located in Tahkenitch Lake, where it is impracticable to establish a permanent monument.</p>   |
| 10.05  | <p>From the center W 1/16 sec. cor. of sec. 29.</p> <p>N. 0° 22' W., on the N. and S. center line of the NW 1/4 of sec. 29.</p> <p>Descend 10 ft. over open rolling sand dunes.</p> <p>Point for the center S-NW 1/64 sec. cor. of sec. 29.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in concrete, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <p>S 29<br/>C-S-NW<br/>1/64<br/>1982</p> </div> <p style="margin-left: 40px;">No suitable trees available.</p> <p style="margin-left: 40px;">Set a steel fence post alongside iron post.</p> <p>Continue over sand dunes.</p>                                    |
| 20.10  | <p>Point for the NW 1/16 sec. cor. of sec. 29, at intersection with the E. and W. center line of the NW 1/4.</p> <p>Set an aluminum rod, 8 ft. long, 5/8 in. diam., 7 1/2 ft. in the ground, in concrete, with aluminum cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <p>NW 1/16 S 29<br/>1982</p> </div> <p style="margin-left: 40px;">No suitable trees available.</p> <p style="margin-left: 40px;">Set a steel fence post alongside aluminum rod.</p> <p>Continue over sand dunes.</p>   |
| 40.19  | <p>The W 1/16 sec. cor. of secs. 20 and 29.</p>   |