

County Surveyor's Record, Douglas County, Oregon

17160

Subdivision of Sec. 29,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
20.14	<p style="text-align: center;">S 29 SE-NW 1/64 1982</p> <p>No suitable trees available.</p> <p>Set a steel fence post alongside aluminum rod.</p> <p>Ascend 25 ft. over rolling sand dunes.</p> <p>The center E-NW 1/64 sec. cor. of sec. 29.</p>
7.605	<p>From the center S-N 1/64 sec. cor. of sec. 29.</p> <p>S. 88° 32' W., on the E. and W. center line of the SE 1/4 of the NW 1/4 of sec. 29.</p> <p>Descend 55 ft. over open rolling sand dunes.</p> <p>Point for the 1/1024 sec. cor. of sec. 29.</p> <p>Set an aluminum rod, 23 ft. long, 5/8 in. diam., 22 1/2 ft. in the ground, in concrete, with aluminum cap mkd.</p> <p style="text-align: center;">1/1024 1982</p> <p>No suitable trees available.</p> <p>Set a steel fence post alongside aluminum rod.</p> <p>Descend 25 ft. over rolling sand dunes.</p>
10.14	<p>The SE-NW 1/64 sec. cor. of sec. 29.</p> <p>Descend 25 ft. over open rolling sand dunes.</p>
20.28	<p>The center S-NW 1/64 sec. cor. of sec. 29.</p>
10.075	<p>From the 1/1024 sec. cor. on the E. and W. center line of the SE 1/4 of the NW 1/4 of sec. 29.</p> <p>N. 0° 20' W., on the N. and S. center line of the W 1/2 of the NE 1/4 of the SE 1/4 of the NW 1/4 of sec. 29.</p> <p>Over open rolling sand dunes.</p> <p>The 1/1024 sec. cor. on the E. and W. center line of the NW 1/4 of sec. 29.</p>
<p>Subdivision of Section 32, T. 20 S., R. 12 W., Willamette Meridian, Oregon</p>	
<p>From the 1/4 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;">T 20 S R 12 W 1/4 $\frac{S 32}{S 5}$ T 21 S 1981</p>	