

County Surveyor's Record, Douglas County, Oregon

17161

Subdivision of Sec. 32,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which bearing trees mkd. by Goodson, McIntyre, and McMullin</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 81° E., 16 1/2 lks. dist., with scribe marks 1/4 S5 BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 0 1/4° W., 12 1/2 lks. dist., with scribe marks 1/4 S32 BT visible on open blaze.</p> <p>N. 0° 20' W., on the N. and S. center line of sec. 32.</p> <p>Ascend 70 ft. over SW. slope, through moderate timber and dense undergrowth.</p>
3.00	Top of ascent, slopes W.; desc. 130 ft. over broken NW. slope.
8.20	Bottom of descent, slopes NE.; continue over nearly level broken E. slope.
35.90	Ravine, drians S. 50° E.; asc. 150 ft. over SW. slope, also leave timber and undergrowth, edge bears N. 50° W. and S. 50° E.; enter rolling sand dunes with scattering timber and undergrowth.
40.48	<p>Point for the center 1/4 sec. cor. of sec. 32, at intersection with the E. and W. center line.</p> <p>Set an aluminum rod, 18 ft. long, 5/8 in. diam., 18 ft. in the ground, in concrete, with aluminum cap mkd.</p> <p style="text-align: center;">T 20 S R 12 W C 1/4 S 32 1981</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 70 3/4° W., 22 1/2 lks. dist., mkd. C 1/4 S32 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 22° W., 60 lks. dist., mkd. C 1/4 S32 BT.</p> <p style="padding-left: 40px;">Set an iron rod, 10 ft. long, 1/2 in. diam., 2 ft. in the ground, alongside aluminum rod.</p> <p>Ascend 40 ft. over S. slope.</p>
45.50	Top of ascent, slopes W.; desc. 140 ft. over rolling sand dunes.
80.51	The 1/4 sec. cor. of secs. 29 and 32.
	<p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>S. 89° 21' W., on the E. and W. center line of sec. 32.</p> <p>Ascend 55 ft. over NE. slope, through moderate timber and dense undergrowth.</p>
2.00	Spur, slopes N.; desc. 70 ft. over broken NW. slope.
19.84	<p>Point for the center E 1/16 sec. cor. of sec. 32.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with aluminum cap mkd.</p>