County Surveyor's Record, Douglas County, Oregon

17162

Subdivision of Sec. 32,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
	C $\frac{\text{E 1/16}}{\text{S 32}}$ C 1981
	from which
	A fir, 11 ins. diam., bears S. 74 1/2° E., 78 1/2 lks. dist., mkd. CE 1/16 S32 BT.
	A fir, 10 ins. diam., bears N. 27° W., 17 1/2 lks. dist., mkd. CE 1/16 S32 BT.
	From this point, a point established by person(s) unknown, bears N. 43° 14' E., 1.45 chs. dist., monumented with an iron pipe, 2 ins. diam., firmly set, projecting 18 ins. above ground.
	Descend 70 ft. over broken NW. slope.
26.60	U.S. Highway No. 101, asphalt surface, 50 lks. wide, bears NE. and SE., in curve.
27.90	Creek, 4 lks. wide, course N. 30° W.; asc. 270 ft. over SE. slope.
38.50	Top of ascent, slopes S.; desc. slightly over SW. slope, also leave timber and undergrowth, edge bears N. and S.; enter open rolling sand dunes with scattering timber and undergrowth.
39.68	The center 1/4 sec. cor. of sec. 32.
	Descend 160 ft. over rolling sand dunes.
79.88	The 1/4 sec. cor. of secs. 31 and 32.
	From the center E 1/16 sec. cor. of sec. 32.
	N. 0° 13' E., on the N. and S. center line of the NE 1/4 of sec. 32.
	Descend 75 ft. over broken NW. slope, through moderate timber and undergrowth.
16.50	Creek, 10 lks. wide, course N. 10° E.; asc. slightly over nearly level ground.
18.55	U.S. Highway No. 101, asphalt surface, 50 lks. wide, bears N. 20° E. and S. 20° W.
40.09	The E 1/16 sec. cor. of secs. 29 and 32.
	From the E 1/16 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with aluminum cap mkd.
	E 1/16 $\frac{\text{S 32}}{\text{S 5}}$ 1981
	from which bearing trees mkd. by Goodson, McIntyre, and McMullin
	A spruce, 9 ins. diam., bears S. 10° E., 21 lks. dist., with scribe marks E 1/16 S5 BT visible on open blaze.