17166

Retracement of Portion of Meanders of
Tahkenitch Lake and Tahkenitch Creek,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS			
	S. 86° 28' W.,	3.07 chs.	
	N. 14° 09' W.,	2.02 chs.	
	N. 3° 16' W.,	5.04 chs.	
	N. 12° 11' W.,	5.06 chs.	
	N. 34° 50' W.,	5.09 chs.	
	N. 55° 24' W.,	5.11 chs.	
	N. 70° 04' W.,	5.12 chs.	At 1.60 chs.; the special meander cor. on the N. and S. center line of the SW 1/4 of sec. 20.
	N. 55° 24' W.,	5.11 chs.	
	S. 88° 26' W.,	3.07 chs.	
	S. 9° 48' E.,	5.93 chs.	
	N. 34° 50' W.,	3.05 chs.	
	N. 51° 30' W.,	5.11 chs.	
	N. 78° 52' W.,	5.12 chs.	At end of course, the true point for the meander cor. of secs. 19 and 20, on the right bank of Tahkenitch Creek.

Survey of Parcel A in Section 29,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

Beginning at the E 1/16 sec. cor. of secs. 29 and 32, identical with Angle Point No. 1 of Parcel A, hereinbefore described.

From this cor., a point established by person(s) unknown, bears N. 33° 45' E., 0.855 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 1 in. above ground.

Thence N. 89° 16' E., bet. secs. 29 and 32 on line 1-2 of Parcel A.

Over nearly level land, through scattering timber and dense undergrowth.

1.41 Point for Angle Point No. 2 of Parcel A, determined at intersection with the westerly right-of-way of U.S. Highway No. 101.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

PARCEL A
AP 2
1982

T 20 S
R 12 W
S 29

Set a steel fence post alongside aluminum post.