

County Surveyor's Record, Douglas County, Oregon

17168

Survey of Parcel A in Sec. 29,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS
2.652

Point for Angle Point No. 6 of Parcel A, determined at deed distance from Angle Point No. 5 of Parcel A, and on the 40 ft. westerly right-of-way of U.S. Highway No. 101.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 32 ins. in the ground, the top 4 ins. below the surface, with aluminum cap mkd.

PARCEL A	T 20 S
AP 6	R 12 W
	S 29
1982	

Set a steel fence post alongside aluminum rod.

Thence N. 4° 23' E., on line 6-7 of Parcel A.

Over level ground, across gravelled driveway, on the 40 ft. westerly right-of-way of U.S. Highway No. 101.

0.545

Point for Angle Point No. 7 of Parcel A, determined at deed distance from Angle Point No. 6 of Parcel A, and on the 40 ft. westerly right-of-way of U.S. Highway No. 101.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with aluminum cap mkd.

	T 20 S
	R 12 W
AP 7	S 29
PARCEL A	
1982	

Thence N. 88° 13' W., on line 7-8 of Parcel A.

Over level ground, along fence line along N. edge of gravelled driveway, bears N. 88 1/4° W. and S. 88 1/4° E.

2.273

Point for Angle Point No. 8 of Parcel A, determined at deed distance from Angle Point No. 7 of Parcel A.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 32 ins. in the ground, the top 4 ins. below the surface, with aluminum cap mkd.

	T 20 S
	R 12 W
AP 8	S 29
PARCEL A	
1982	

Corner is located in lawn.

Thence N. 4° 23' E., on line 8-9 of Parcel A.

Over nearly level land, across landscaped area and lawn.

3.03

Point for Angle Point No. 9 of Parcel A, determined at deed distance from Angle Point No. 8 of Parcel A.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.