

County Surveyor's Record, Douglas County, Oregon

17178

Survey of Parcel E, Section 20,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS

17.535

Point for Angle Point No. 4 of Parcel E.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 20 S	PARCEL E
R 12 W	AP 4
S 20	
1982	

from which

A spruce, 13 ins. diam., bears N. 27° E., 29 lks. dist., mkd. AP4 PAR E BT.

A pine, 15 ins. diam., bears N. 56 1/2° W., 70 lks. dist., mkd. AP S20 BT.

From this point, a point of no known record, bears East, 0.73 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set flush with the ground.

Thence N. 88° 12' E., on line 4-5 of Parcel E, and parallel with the E. and W. center line of sec. 20.

Ascend over broken SW. slope, through moderate timber and dense undergrowth.

7.00

Point for Angle Point No. 5 of Parcel E, determined at deed distance from Angle Point No. 6 of Parcel E.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S	PARCEL E
R 12 W	AP 5
S 20	
1982	

from which

A fir, 9 ins. diam., bears S. 49 1/2° E., 15 lks. dist., mkd. AP5 PAR E BT.

A spruce, 13 ins. diam., bears S. 20 1/2° W., 31 1/2 lks. dist., mkd. AP S20 BT.

Thence S. 0° 27' E., on line 5-6 of Parcel E, parallel with the N. and S. center line of the NE 1/4 of sec. 20.

Descend over broken S. slope, through moderate timber and undergrowth.

2.75

Ravine, drains S. 45° W.; asc. over NW. slope.

4.545

Intersect the E. and W. center line of sec. 20, and point for Angle Point No. 6 of Parcel E, determined at deed distance from the 1/4 sec. cor. of secs. 20 and 21.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

T 20 S	PARCEL E
R 12 W	AP 6
S 20	
1982	