Survey of Parcel E, Section 20,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
	from which
	A spruce, 8 ins. diam., bears N. 40° E., 28 lks. dist., mkd. AP6 PAR E BT.
	A spruce, 9 ins. diam., bears S. 26 1/2° E., 19 1/2 lks. dist., mkd. AP S20 BT.
	Thence N. 88° 12' E., on line 6-7 of Parcel E, on the E. and W. center line of sec. 20.
13.40	The 1/4 sec. cor. of secs. 20 and 21, identical with Angle Point No. 7 of Parcel E.
	Thence N. 0° 34' W., on line 7-1 of Parcel E, on the line bet. secs. 20 and 21.
20.075	The N 1/16 sec. cor. of secs. 20 and 21.
28.33	Angle Point No. 1 of Parcel E and point of beginning.

Survey of Parcel F in Section 20
T. 20 S., R. 12 W., Willamette Meridian, Oregon

Beginning at a point on line 1-2 of Parcel E, described as the point of beginning in the Individual Warranty Deed, dated October 11, 1979, conveying from Louisa E. Slonecker to the United States of America, the following described tract of land in sec. 20, hereinafter identified as Parcel F. This position is designated Angle Point No. 1 of Parcel F, and was determined at deed distance from Angle Point No. 1 of Parcel E, hereinbefore described.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

PARCEL F | T 20 S
R 12 W
AP 1 | S 20
PARCEL E
1982

from which

A cedar, 18 ins. diam., bears N. 17 3/4° E., 41 lks. dist., mkd. AP S20 BT.

Set a steel fence post alongside iron post.

Thence North, on line 1-2 of Parcel F.

Descend over NW. slope, through scattering timber and dense undergrowth.

2.392 Point for Angle Point No. 2 of Parcel F, determined at deed distance from Angle Point No. 1 of Parcel F.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S
AP 2 | R 12 W
PARCEL F | S 20
1982