

County Surveyor's Record, Douglas County, Oregon

17180

Survey of Parcel F, Section 20,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 28 ins. diam., bears S. 22 3/4° W., 26 1/2 lks. dist., mkd. AP1 PAR F BT.

Set a steel fence post alongside iron post.

Thence N. 28° 00' W., on line 2-3 of Parcel F.

Descent slightly across marshy ground.

2.721

Point for Angle Point No. 3 of Parcel F, determined at deed distance from Angle Point No. 2 of Parcel F.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 12 W
AP 3 S 20
PARCEL F
1982

from which

A fir, 10 ins. diam., bears S. 57 1/2° W., 86 lks. dist., mkd. AP3 PAR F BT.

Set a steel fence post alongside iron post.

The corner is located on high water line, on S. shore of an unnamed seasonal lake.

Thence on line 3-4 of Parcel F, along the high water line of an unnamed lake.

N. 22° 27' W., 0.98 chs.

N. 33° 59' W., 0.44 chs.

N. 52° 24' W., 0.565 chs.

N. 86° 34' W., 0.905 chs.

West, 0.555 chs.

S. 58° 04' W., 0.325 ch.

S. 46° 26' W., 2.17 chs.

At end of course, point for Angle Point No. 4 of Parcel F, on the high water line of unnamed lake.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, in concrete, with aluminum cap mkd.

T 20 S R 12 W
S 20
AP 4
PARCEL F
1982

Thence West, on line 4-5 of Parcel F.

Descend slightly in lake.