

County Surveyor's Record, Douglas County, Oregon

17186

Dependent Resurvey, Portion of S. Bdy.,
T. 21 S., R. 12 W., Willamette Meridian, Oregon

CHAINS

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 21 S	R 12 W
MC	S 32
	S 5
	T 22 S
	1981

from which

A spruce, 30 ins. diam., bears S. 59 1/4° E., 13 lks. dist., mkd. T22S R12W S5 MC BT.

A spruce, 11 ins. diam., bears N. 2° W., 58 1/2 lks. dist., mkd. T21S R12W S32 MC BT.

The corner is located on the left bank of Umpqua River, bears N. and S., course S.

N. 89° 22' W., beg. secs. 5 and 32, marking the true line.

Thence across Umpqua River.

18.21

Point for the cor. of secs. 5, 6, 31, and 32, at record distance, located in Umpqua River.

N. 89° 22' W., bet. secs. 6 and 31.

Continue across river.

34.45

Right bank of the Umpqua River, bears N. and S.; asc. 20 ft. over sand dunes.

37.50

Point for the meander cor. of secs. 6 and 31, at record distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in concrete, with aluminum cap mkd.

T 21 S	R 12 W
	S 31
	S 6
	T 22 S
	1981

No suitable trees available within limits.

Set a steel fence post alongside aluminum post.

Continue over sand dunes.

40.00

Point for the 1/4 sec. cor. of secs. 6 and 31, at record distance; there is no remaining evidence of the original corner.

Set an aluminum rod, 13 ft. long, 5/8 ins. diam., 12 ft. in the ground, in concrete, with aluminum cap mkd.

T 21 S	R 12 W
1/4	S 31
	S 6
	T 22 S
	1981