

County Surveyor's Record, Douglas County, Oregon

17187

Dependent Resurvey, Portion of S. Bdy.,
T. 21 S., R. 12 W., Willamette Meridian, Oregon

CHAINS

80.00

No suitable trees available within limits.

Set a steel fence post alongside aluminum rod.

Continue over rolling sand dunes.

Point for the cor. of Tps. 21 and 22 S., Rs. 12 and 13 W., at record distance longitudinally from the meander cor. of secs. 5 and 32, on the left bank of the Umpqua River, S. bdy. of T. 21 S., R. 12 W. and record distance latitudinally from the cor. of secs. 7, 12, 13, and 18, on the E. bdy. of T. 22 S., R. 13 W.; there is no remaining evidence of the original corner.

Set an aluminum rod, 10 ft. long, 5/8 in. diam., 9 ft. in the ground, in concrete, with aluminum cap mkd.

T 21 S
R 13 W R 12 W
S 36 | S 31
S 1 | S 6
T 22 S
1981

No suitable trees available within limits.

Set a steel fence post alongside aluminum rod.

Land, rolling dunes.
Soil, sand.
Vegetation, marsh grass.

Dependent Resurvey of a Portion of the East Boundary,
T. 22 S., R. 13 W., Willamette Meridian, Oregon.

(Restoring the survey by Harvey Gordon,
U.S. Deputy Surveyor, in 1857)

From the cor. of secs. 7, 12, 13, and 18, perpetuated and recorded by the Oregon State Highway Department, in 1954, from original evidence no longer in existence, and further perpetuated and recorded by James W. Byron, County Surveyor, in 1967, monumented with a P.K. nail, firmly set flush with the asphalt surface of U.S. Highway No. 101, 70 lks. wide, bears N. 25° E. and S. 25° W., from which reference monuments established by the State Highway Department:

A railroad spike, firmly set in solid rock, bears S. 15° E., 115 lks. dist.

A steel bolt, 3/4 in. diam., firmly set in solid rock, bears N. 85° W., 66 1/2 lks. dist.

and new reference monuments

An aluminum rod, 4 ft. long, 5/8 in. diam., set 3 ft. in the ground, for a reference monument, bears N. 82 3/4° E., 77 1/2 lks. dist., with aluminum cap mkd. T22S R12W S7 RM 1981 and an arrow pointing to the corner.

An aluminum rod, 4 ft. long, 5/8 in. diam., set 3 ft. in the ground, for a reference monument, bears S. 75 1/2° W., 110 lks. dist., with aluminum cap mkd. T22S R13W S13 RM 1981 and an arrow pointing to the corner.