


County Surveyor's Record, Douglas County, Oregon

17189

Dependent Resurvey, Portion of E. Bdy.,
T. 22 S., R. 13 W., Willamette Meridian, Oregon

CHAINS

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in concrete, with aluminum cap mkd.



No suitable trees available within limits.

Set a steel fence post alongside aluminum post.

Ascend slightly over rolling sand dunes.

80.00

The cor. of Tps. 21 and 22 S., Rs. 12 and 13 W.

Land, S1/2 mile, Winchester Bay, N1/2 mile, rolling dunes.
Soil, N1/2 mile, sand.
Vegetation, marsh grass.

Dependent Resurvey of the North Boundary,
T. 22 S., R. 13 W., Willamette Meridian, Oregon

(Restoring the survey by Harvey Gordon,
U.S. Deputy Surveyor, in 1857)

From the cor. of Tps. 21 and 22 S., Rs. 12 and 13 W.


West, bet. secs. 1 and 36, marking the true line.

Thence across nearly level sand dunes.

37.17

Point for the meander cor. of secs. 1 and 36 on the shore of the Pacific Ocean, at record distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in concrete, with aluminum cap mkd.



No suitable trees available within limits.

This meander corner is located 13.00 chs. East of mean high tide and shore of the Pacific Ocean, which bears N. 10° E. and S. 10° W.

Land, nearly level dunes.
Soil, sand.
Vegetation, marsh grass.

Dependent Resurvey of a Portion of the West Boundary,
T. 21 S., R. 12 W., Willamette Meridian, Oregon

(Restoring the survey by Harvey Gordon,
U.S. Deputy Surveyor, in 1857)