

County Surveyor's Record, Douglas County, Oregon

17190

Dependent Resurvey, Portion of W. Bdy.,
T. 21 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
40.00	<p>From the cor. of Tps. 21 and 22 S., Rs. 12 and 13 W. North, bet. secs. 31 and 36, marking the true line. Over nearly level sand dunes.</p> <p>Point for the 1/4 sec. cor. of secs. 31 and 36, at record distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum rod, 10 ft. long, 5/8 in. diam., 9 ft. in the ground, in concrete, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T 21 S R 13 W R 12 W 1/4 S 36 S 31 1981 </div> <p>No suitable trees available within limits.</p> <p>Set a steel fence post alongside aluminum rod.</p> <p>Continue over nearly level sand dunes.</p>
80.00	<p>Point for the cor. of secs. 25, 30, 31, and 36, at record distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, in concrete, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T 21 S R 13 W R 12 W S 25 S 30 S 36 S 31 1981 </div> <p>No suitable trees available within limits.</p> <p>Set a steel fence post alongside aluminum post.</p> <p>Land, level. Soil, sand. Vegetation, marsh grass.</p>
40.00	<p>North, bet. secs. 25 and 30.</p> <p>Continue over nearly level sand dunes.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 30, at record distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in concrete, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T 21 S R 13 W R 12 W 1/4 S 25 S 30 1981 </div> <p>No suitable trees available within limits.</p> <p>Set a steel fence post alongside aluminum post.</p>