

County Surveyor's Record, Douglas County, Oregon

17191

Dependent Resurvey, Portion of W. Bdy.,
T. 21 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
80.00	<p>Continue over nearly level sand dunes.</p> <p>Point for the cor. of secs. 19, 24, 25, and 30, at record distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in concrete, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 21 S R 13 W R 12 W S 24 S 19 S 25 S 30 1981</p> </div> <p>No suitable trees available within limits.</p> <p>Set a steel fence post alongside aluminum post.</p> <p>Land, rolling dunes. Soil, sandy. Vegetation, marsh grass.</p>
31.65	<p>North, bet. secs. 19 and 24.</p> <p>Continue over rolling sand dunes.</p> <p>Sand road, 20 lks. wide, bears N. 25° W. and S. 25° E.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, at record distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in concrete, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 21 S R 13 W R 12 W 1/4 S 24 S 19 1981</p> </div> <p>No suitable trees available within limits.</p> <p>Set a steel fence post alongside aluminum post.</p>
44.50	<p>Continue over rolling sand dunes.</p> <p>Point for the meander cor. of secs. 19 and 24, on the shore of the Pacific Ocean, at record distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in concrete, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>MC S 24 S 19 R 13 W R 12 W T 21 S 1981</p> </div> <p>No suitable trees available within limits.</p> <p>Set a steel fence post alongside aluminum post.</p>