

County Surveyor's Record, Douglas County, Oregon

17192

Dependent Resurvey, Portion of W. Bdy.,
T. 21 S., R. 12 W., Willamette Meridian, Oregon

CHAINS

This corner is located 34.35 chs. South of the mean high tide and shore of the Pacific Ocean, which bears N. 10° E. and S. 10° W.

Land, rolling dunes.
Soil, sandy.
Timber, dwarf pine; undergrowth, marsh grass and manzanita.

Dependent Resurvey of a Portion of the North Boundary,
T. 21 S., R. 12 W., Willamette Meridian, Oregon

(Restoring the survey by Harvey Gordon,
U.S. Deputy Surveyor, in 1857)

From the cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., perpetuated and recorded by W.G. Corbitt, for Crown Zellerbach Corporation, in 1943, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 4 ins. above ground, from which the remains of an original bearing tree:

A decayed hemlock stump, 12 ins. diam., bears N. 63° E., 75 lks. dist., no marks visible.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, directly over iron pipe, with aluminum cap mkd.

T	20	S	R	12	W
	S	32	S	33	
	S	5	S	4	
					T 21 S
					1981

from which new bearing trees

An alder, 5 ins. diam., bears N. 35° E., 47 lks. dist., mkd. T20S R12W S33 BT.

A spruce, 11 ins. diam., bears S. 61 1/4° E., 51 lks. dist., mkd. T21S R12W S4 BT.

A spruce, 13 ins. diam., bears S. 70° W., 127 lks. dist., mkd. T21S R12W S5 BT.

A spruce, 10 ins. diam., bears N. 68 1/4° W., 135 lks. dist., mkd. T20S R12W S32 BT.

S. 88° 44' W., bet. secs. 5 and 32, marking and blazing the true line.

Over nearly level land, through heavy timber and light undergrowth.

0.85 Creek, 15 lks. wide, course N.; asc. 345 ft. over broken NE. slope.

19.505 Point for the E 1/16 sec. cor. of secs. 5 and 32.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with aluminum cap mkd.