

# County Surveyor's Record, Douglas County, Oregon

17193

Dependent Resurvey, Portion of N. Bdy.,  
T. 21 S., R. 12 W., Willamette Meridian, Oregon

CHAINS

E 1/16  $\frac{S\ 32}{S\ 5}$   
1981

from which

A spruce, 9 ins. diam., bears S. 10° E., 21 lks. dist., mkd. E1/16 S5 BT.

A spruce, 8 ins. diam., bears N. 38 1/2° W., 8 lks. dist., mkd. E1/16 S32 BT.

The corner is located on spur, slopes N.; desc. 165 ft. over broken NW. slope.

23.95 Ravine, drains N. 60° W.; asc. 15 ft. over N. slope.

26.35 Spur ridge, slopes NW.; desc. 100 ft. over W. slope.

28.80 Ravine, drains N.; asc. 135 ft. over E. slope.

33.85 Ridge, bears N. and S.; desc. 15 ft. over W. slope.


34.51 The witness cor. to the 1/4 sec. cor. of secs. 5 and 32, perpetuated and recorded by W.C. Corbitt, for Crown Zellerbach Corporation, in 1943, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, the top 12 ins. below the surface of the ground, from which the remains of the original bearing trees:

A sawed fir stump, 58 ins. diam., bears S. 65° W., 38 lks. dist., with partially healed blaze, no marks visible.

A sawed fir stump, 26 ins. diam., bears N. 77° W., 19 lks. dist., no marks visible.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, directly over the iron pipe, with aluminum cap mkd.



from which

A fir, 8 ins. diam., bears N. 58 1/2° E., 15 lks. dist., mkd. X BT.

A fir, 8 ins. diam., bears S. 58 1/4° E., 16 lks. dist., mkd. X BT.

This corner now becomes an angle point.

West, beginning new measurement.

Descend 170 ft. over broken W. slope.

4.00 Creek, 1 lk. wide, course S. 45° W.; desc. slightly along S. slope.

4.50 True point for the 1/4 sec. cor. of secs. 5 and 32, at record distance from the original witness corner.