

# County Surveyor's Record, Douglas County, Oregon

17194

Dependent Resurvey, Portion of N. Bdy.,  
T. 21 S., R. 12 W., Willamette Meridian, Oregon

**CHAINS**

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 20 S R 12 W  
1/4  $\frac{S\ 32}{S\ 5}$   
T 21 S  
1981

from which

A fir, 10 ins. diam., bears S. 81° E., 16 1/2 lks. dist., mkd. 1/4 S5 BT.

A fir, 11 ins. diam., bears N. 0 1/4° W., 12 1/2 lks. dist., mkd. 1/4 S32 BT.

West, beginning new measurement.

Descend 55 ft. over SW. slope.

- 4.20 Creek, 2 lks. wide, course N. 45° E.; asc. 70 ft. over SE. slope.
- 11.25 Spur, slopes N.; desc. 50 ft. over broken NW. slope.
- 14.00 Creek, 2 lks. wide, course N. 45° E.; asc. 265 ft. over SE. slope.
- 23.00 Ridge, bears N. and S.; desc. 100 ft. over W. slope.
- 26.20 Draw, drains N. 25° W.; asc. 45 ft. over broken NE. slope changing to N. slope.
- 30.00 Spur, slopes N. 40° W.; desc. 285 ft. over W. slope.
- 40.00 Point for the cor. of secs. 5, 6, 31, and 32, at record distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with aluminum cap mkd.

T 20 S R 12 W  
 $\frac{S\ 31}{S\ 6} \mid \frac{S\ 32}{S\ 5}$   
T 21 S  
1981

from which

A spruce, 32 ins. diam., bears N. 59° E., 75 1/2 lks. dist., mkd. T20S R12W S32 BT.

A spruce, 22 ins. diam., bears S. 16° E., 54 1/2 lks. dist., mkd. T21S R12W S5 BT.

A spruce, 19 ins. diam., bears S. 56° W., 37 lks. dist., mkd. T21S R12W S6 BT.

A spruce, 17 ins. diam., bears N. 27° W., 17 1/2 lks. dist., mkd. T20S R12W S31 BT.

Land, rolling hills.  
Soil, sandy loam.