

# County Surveyor's Record, Douglas County, Oregon

17199

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 21 S., R. 12 W., Willamette Meridian, Oregon

CHAINS

From the point for the cor. of secs. 17, 18, 19, and 20, at record distance longitudinally from the meander cor. of secs. 18 and 19, on the shore of the Pacific Ocean, and record distance latitudinally from the cor. of secs. 7, 8, 17, and 18; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 21 S R 12 W  
S 18 | S 17  
S 19 | S 20  
1981

from which

A hemlock, 8 ins. diam., bears N. 80 1/2° E., 10 1/2 lks. dist., mkd. T21S R12W S17 BT.

A fir, 8 ins. diam., bears S. 35 1/2° E., 18 lks. dist., mkd. T21S R12W S20 BT.

A pine, 12 ins. diam., bears S. 8° W., 15 1/2 lks. dist., mkd. T21S R12W S19 BT.

A fir, 9 ins. diam., bears N. 62° W., 47 1/2 lks. dist., mkd. T21S R12W S18 BT.

South, bet. secs. 19 and 20.

Ascend 5 ft. over gentle NE. slope, through light timber and dense undergrowth.

1.00 Spur, slopes SE.; desc. 235 ft. over precipitous SE. slope.

7.54 Point selected for the witness cor. to the meander cor. of secs. 19 and 20, on the right bank of the Umpqua River.

Set an aluminum rod, 4 ft. long, 3/4 ins. diam., 3 1/2 ft. in the ground, and in a collar of stone, with aluminum cap mkd.

WC  
T 21 S R 12 W  
S 19 | S 20  
↓  
MC  
1981

from which

A spruce, 5 ins. diam., bears N. 76° E., 22 1/2 lks. dist., mkd. X BT.

An XBO, chiseled on a sandstone bluff, 12 ft. high, bears S. 80° W., 49 1/2 lks. dist.

The corner is located on the right bank of the Umpqua River, which bears N. 40° E. and S. 40° W.

Thence over river.

9.00 True point for the meander cor. of secs. 19 and 20, on the right bank of the Umpqua River, at record distance; there is no remaining evidence of the original corner. This point falls in the tide plain of the river, where it is impracticable to establish a permanent monument.