

County Surveyor's Record, Douglas County, Oregon

17205

Dependent Resurvey, Portion of Subdivisional Lines,
T. 21 S., R. 12 W., Willamette Meridian, Oregon

CHAINS								
1.80	Enter marsh, edge bears N. 50° E. and S. 50° W.							
5.40	Leave marsh, edge bears N. 20° E. and S. 20° W.; asc. 20 ft. over SE. slope.							
10.70	Top of ascent, slopes S.; desc. 30 ft. over SW. slope.							
14.10	Enter marsh, edge bears N. 40° W. and S. 40° E.							
26.40	Leave marsh, edge bears N. and S.; asc. 130 ft. over E. slope, changing to NE. slope.							
34.405	Intersect the N. bdy. of Donation Land Claim No. 39. Point for the crossing closing cor. of secs. 8 and 17, with the N. bdy. of Claim No. 39. Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with aluminum cap mkd. <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr> <td style="padding: 0 10px;">CCC</td> <td style="text-align: center; border: none;"> $\frac{S\ 8}{S\ 17}$ </td> <td style="padding: 0 10px; border: none;">DLC</td> </tr> <tr> <td></td> <td style="text-align: center; border: none;">1981</td> <td style="text-align: center; border: none;">39</td> </tr> </table> </div> from which A spruce, 10 ins. diam., bears N. 87 1/2° E., 18 lks. dist., mkd. DLC 39 S8 CCC BT. A spruce, 10 ins. diam., bears S. 10 1/2° E., 37 lks. dist., mkd. DLC 39 S17 CCC BT. From this point, the NE. cor. of Donation Land Claim No. 39, bears N. 67° 38' E., 23.41 chs. dist., hereinafter described. Ascend 25 ft. over NE. slope.	CCC	$\frac{S\ 8}{S\ 17}$	DLC		1981	39	
CCC	$\frac{S\ 8}{S\ 17}$	DLC						
	1981	39						
36.05	Top of ascent, slopes SE.; desc. 30 ft. over gentle SW. slope, changing to S. slope.							
40.59	The 1/4 sec. cor. of secs. 8 and 17, established by person(s) unknown, at record bearing and distance from the original witness cor. to the 1/4 sec. cor. of secs. 8 and 17, and is accepted as the corner, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, from which a bearing tree mkd. by person(s) unknown: <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr> <td style="padding: 0 10px;">A hemlock, 30 ins. diam., bears S. 9° E., 63 1/2 lks. dist., with healed blaze.</td> </tr> </table> </div> At the corner point Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over the iron pipe, with aluminum cap mkd. <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr> <td style="padding: 0 10px;">T 21 S</td> <td style="padding: 0 10px;">R 12 W</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="text-align: center; border: none;"> $\frac{S\ 8}{S\ 17}$ </td> </tr> <tr> <td></td> <td style="text-align: center; border: none;">1981</td> </tr> </table> </div> from which new bearing trees A hemlock, 40 ins. diam., bears N. 72 1/4° E., 67 lks. dist., mkd. 1/4 S8 BT.	A hemlock, 30 ins. diam., bears S. 9° E., 63 1/2 lks. dist., with healed blaze.	T 21 S	R 12 W	1/4	$\frac{S\ 8}{S\ 17}$		1981
A hemlock, 30 ins. diam., bears S. 9° E., 63 1/2 lks. dist., with healed blaze.								
T 21 S	R 12 W							
1/4	$\frac{S\ 8}{S\ 17}$							
	1981							