

County Surveyor's Record, Douglas County, Oregon

17218

Subdivision of Sec. 5,
T. 21 S., R. 12 W., Willamette Meridian, Oregon

CHAINS

43.10 Creek, 2 lks. wide, course S. 85° W.; asc. 70 ft. over SW. slope.

45.10 Spur, slopes S. 50° W.; desc. 25 ft. over NW. slope.

46.90 Creek, 1 lk. wide, course S. 40° W.; asc. 160 ft. over SE. slope.

52.55 Spur, slopes S. 65° W.; desc. 140 ft. over steep N. slope.

56.60 Draw, slopes N. 50° W.; asc. 25 ft. over SW. slope.

59.30 Spur, slopes N. 45° W.; desc. 115 ft. over N. slope.

62.65 Creek, 1 lk. wide, bears N. 35° W.; asc. 40 ft. along W. slope.

65.55 Spur, slopes N. 50° W.; desc. 50 ft. over N. slope.

67.25 Creek, 1 lk. wide, course N. 70° W.; asc. 35 ft. over SW. slope.

70.15 Spur, slopes NW.; desc. 95 ft. over N. slope.

74.55 Creek, 1 lk. wide, course W.; asc. 15 ft. over S. slope.

75.69 The 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp.

From the 1/4 sec. cor. of secs. 4 and 5.

N. 87° 23' W., on the E. and W. center line of sec. 5.

Ascend 25 ft. over SE. slope, through heavy timber and moderate undergrowth.

0.65 Ridge, bears N. and S.; desc. 210 ft. over gently W. slope.

3.35 U.S. Highway 101, asphalt surfaced, 70 lks. wide, bears N. 10° E. and S. 10° W.

11.40 Creek, 3 lks. wide, course N. 5° W.; asc. 135 ft. over NE. slope.

16.75 Spur, slopes NE.; desc. 110 ft. along steep N. slope, changing to NW. slope.

19.55 Creek, 1 lk. wide, course N. 50° E.; asc. 10 ft. over SE. slope.

19.80 Point for the center E 1/16 sec. cor. of sec. 5.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

C $\frac{E \ 1/16}{S \ 5}$ C
1981

from which

A hemlock, 12 ins. diam., bears N. 73 3/4° E.,
8 1/2 lks. dist., mkd. CE 1/16 S5 BT.

A spruce, 23 ins. diam., bears S. 81 1/4° W., 5 1/2
lks. dist., mkd. CE 1/16 S5 BT.