

County Surveyor's Record, Douglas County, Oregon

17221

Subdivision of Sec. 17,
T. 21 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
	Descend 25 ft. over broken SE. slope.
9.25	Creek, 2 lks. wide, course S. 25° E.; asc. 10 ft. over NE. slope.
10.25	Top of ascent, slopes SE.; desc. 20 ft. over SW. slope
11.20	Creek,, 1 lk. wide, course S. 30° E.; asc. 20 ft. over broken NE. slope.
11.50	Top of ascent, slopes E.; desc. 95 ft. over broken S. slope.
24.05	Creek, 27 lks. wide, course W.; continue over nearly level land.
26.00	Gravelled road, 25 lks. wide, bears N. 85° E. and S. 85° W.
26.35	Creek, 10 lks. wide, course S. 85° W.; asc. 95 ft. over broken NE. slope.
31.85	Dirt road, 15 lks. wide, bears N. 75° W. and S. 75° E.
36.30	Top of ascent, slopes E.; desc. 55 ft. over broken SE. slope.
40.32	Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line. Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd. <div style="text-align: center;"> T 21 S R 12 W C 1/4 S 17 1981 </div> from which A spruce, 95 ins. diam., bears S. 33 1/4° E., 100 lks. dist., mkd. C 1/4 S17 BT. A spruce, 75 ins. diam., bears S. 53 1/2° W., 93 lks. dist., mkd. C 1/4 S17 BT. Descend 85 ft. over SE. slope.
42.975	Point for the witness cor. to the special meander cor. on the N. and S. center line of sec. 17. Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in drill hole, in base of sandstone cliff, with top mkd. <div style="text-align: center;"> WC C S 17 C SMC 1981 </div> from which An XBO, chiseled in a rock face, bears S. 58° E., 5 1/2 lks. dist., An XBO, chiseled in a rock face, bears N. 48° W., 5 1/2 lks. dist.