

County Surveyor's Record, Douglas County, Oregon

17231

T. 21 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, township 21 south, range 7 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The south boundary of the township was surveyed by Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, in 1855.

The east boundary and a portion of the subdivisional lines were surveyed by Laban H. Wheeler, U.S. Deputy Surveyor, in 1883.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions, dated September 15, 1981, for Group Number 1081, Oregon.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations and refer to the true meridian.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming closures were measured twice. Only the lines bounding or crossing public lands were blazed.

The geographic position of the corner of sections 1, 2, 35, and 36, on the south boundary of the township, as scaled from the "DRAIN, OREG." topographic map, prepared by the United States Geological Survey in 1954, is as follows:

Latitude 43° 41.6' N. Longitude 123° 29.1' W.

The mean magnetic declination is 21° E.

Dependent Resurvey of a Portion of the
Subdivisional Lines, T. 21 S., R. 7 W.,
Willamette Meridian, Oregon

(Restoring the survey by Laban H. Wheeler in 1883)

Beginning at the cor. of secs. 1, 2, 35, and 36, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1960, and perpetuated and recorded by Milo E. Godfrey, Deputy Douglas County Surveyor, in 1962, monumented with a 3/4 in. "T" shaped iron rod, firmly set, projecting 2 ins. above the ground, with an aluminum washer mkd. "Wilford N. Haines Survey Point 239", from which the remains of an original bearing tree

A sawed fir stump, 52 ins. diam., bears S. 36° W., 32 lks. dist., with fragmentary scribe marks visible on opened blaze.