

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 21 S., R. 7 W., Willamette Meridian, Oregon

17232

CHAINS

and a bearing tree mkd. by Wheeler

A maple, 23 ins. diam., bears S. 15° E., 22 lks. dist., with fragmentary scribe marks visible on decayed blaze. (Record, 20 lks.)

and bearing trees mkd. by Godfrey

A fir, 30 ins. diam., bears N. 62° E., 80 lks. dist., with fragmentary scribe marks visible on bark blaze.

A cedar, 28 ins. diam., bears N. 34 1/2° W., 79 1/2 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and a tree not of known record

A fir, 44 ins. diam., bears N. 44° W., 71 lks. dist., with fragmentary scribe marks visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 21 S	R 7 W
S 35	S 36
S 2	S 1
T 22 S	R 7 W
1981	

from which new bearing trees

A hemlock, 8 ins. diam., bears S. 43° E., 95 1/2 lks. dist., mkd. T22S R7W S1 BT.

A grand fir, 12 ins. diam., bears S. 86° W., 29 1/2 lks. dist., mkd. T22S R7W S2 BT.

Deposit the "T" shaped iron rod alongside the iron post.

N. 1° 20' E., bet. secs. 35 and 36, marking and blazing the true line.

Ascend 95 ft. over SW. slope, through heavy timber and dense undergrowth.

3.45 Spur, slopes W.; desc. 205 ft. over broken NW. slope.

12.35 Big Tom Folley Creek, 50 lks. wide, course S. 60° W.; asc. 170 ft. over SE. slope.

16.00 Big Tom Folley Creek Road, gravelled, 30 lks. wide, bears N. 70° E. and S. 70° W.

19.41 The S 1/16 sec. cor. of secs. 35 and 36, established by Wilford N. Haines, Registered Land Surveyor No. 239, in 1960, and accepted as the corner, monumented with a 3/4 in. "T" shaped iron rod, firmly set, projecting 4 ins. above the ground, with an aluminum washer mkd. "Wilford N. Haines Survey Point 239", from which bearing trees mkd. by Haines

A fir, 23 ins. diam., bears S. 44° E., 36 lks. dist., with healed blaze.