

# County Surveyor's Record, Douglas County, Oregon

**17233**

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 21 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 40 ins. diam., bears N. 70° W., 32 lks. dist., with scribe marks 1/16 S BT visible on bark blaze.

N. 1° 20' E., beginning new measurement.

Ascend 265 ft. over SE. slope.

17.60 Top of ascent, slopes E.; desc. 5 ft. over NE. slope.

19.41 The 1/4 sec. cor. of secs. 35 and 36, reestablished by proportionate measurement by Wilford N. Haines, Registered Land Surveyor No. 239, in 1960, and accepted as the best available evidence of the position of the original corner, monumented with a 3/4 in. "T" shaped iron rod, firmly set, projecting 4 ins. above the ground, with an aluminum washer mkd. "Wilford N. Haines Survey Point 239", from which a bearing tree mkd. by Haines

*Possible info in F.B.H.-69*

A fir, 46 ins. diam., bears N. 15 3/4° W., 94 lks. dist., with scribe marks 1/4 S BT visible on bark blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

*TNO. OK  
D. BAKER 12-91  
M.H.-26*

T 21 S R 7 W  
1/4  
S 35 S 36  
1981

from which a new bearing tree

A hemlock, 13 ins. diam., bears S. 6 1/2° E., 19 1/2 lks. dist., mkd. 1/4 S36 BT.

Deposit the "T" shaped iron rod alongside the aluminum post.

N. 1° 20' E., beginning new measurement.

Descend 60 ft. over NE. slope.

3.45 Ravine, drains E.; asc. 110 ft. over SE. slope.

14.55 Top of ascent, slopes E.; desc. 35 ft. over NE. slope.

16.05 Creek, 2 lks. wide, course S. 60° E.; asc. 110 ft. over SE. slope.

19.42 The N 1/16 sec. cor. of secs. 35 and 36, established by Wilford N. Haines, Registered Land Surveyor No. 239, in 1960, and accepted as the corner, monumented with a 3/4 in. "T" shaped iron rod, firmly set, projecting 4 ins. above the ground, with aluminum washer mkd. "Wilford N. Haines Survey Point 239", from which bearing trees mkd. by Haines

*Possible info in F.B.H.-69*

A fir, 40 ins. diam., bears N. 23 1/2° E., 123 lks. dist., with scribe marks 1/16 S BT visible on bark blaze.

A fir, 36 ins. diam., bears S. 43° E., 49 1/2 lks. dist., with scribe marks 1/16 S BT visible on bark blaze.