

County Surveyor's Record, Douglas County, Oregon

17235

Dependent Resurvey, Portion of Subdivisional Lines,
T. 21 S., R. 7 W., Willamette Meridian, Oregon

CHAINS
10.80

Spur, slopes S. 80° W.; desc. 240 ft. over NW. slope.

17.00

Ravine, drains N. 60° W.; asc. 140 ft. over SW. slope.

26.75

Spur, slopes NW.; desc. 215 ft. over N. slope.

32.60

Ravine, drains N. 50° W.; desc. 5 ft. over NW. slope.

35.55

Spur, slopes N. 40° W.; desc. 110 ft. over NE. slope.

36.89

Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

*FIND OK 9/92
L. ROBERTS M115-63*

T 21 S R 7 W
 1/4
S 26 | S 25
 1981

from which

A fir, 26 ins. diam., bears N. 65 1/4° E., 27 1/2 lks. dist., mkd. 1/4 S25 BT.

A fir, 5 ins. diam., bears N. 49° W., 24 lks. dist., mkd. 1/4 S26 BT.

Descend 220 ft. over NE. slope.

41.40

Creek, 5 lks. wide, course N. 60° W.; asc. 170 ft. over SW. slope.

47.30

Ravine, drains S. 50° W.; asc. 300 ft. over SW. slope.

73.78

The cor. of secs. 23, 24, 25, and 26, perpetuated and recorded by John M. Powell, Deputy Douglas County Surveyor, in 1970, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 4 ins. above ground, in the root hole of the original corner tree, which is a down fir lying alongside, 53 ins. diam., with fragmentary scribe marks visible on opened blaze, the brass cap on the iron post is mkd.

COUNTY SURVEYORS OFFICE

T 21 S R 7 W
 S 23 | S 24
 S 26 | S 25
 1970

from which the remains of two original bearing trees

A sawed fir stump, 84 ins. diam., bears N. 45° E., 65 lks. dist., with no marks visible.

A fir, 32 ins. diam., bears N. 40° W., 22 lks. dist., with no marks visible.

and bearing trees mkd. by Powell

A fir, 7 ins. diam., bears N. 46 1/2° E., 35 lks. dist., with healed blaze.

A fir, 24 ins. diam., bears S. 6° E., 61 lks. dist., with healed blaze.