

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 21 S., R. 7 W., Willamette Meridian, Oregon

17236

CHAINS	
	<p style="text-align: center;">A fir, 10 ins. diam., bears S. 78 1/2° W., 19 1/2 lks. dist., with healed blaze.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, yew, oak, maple, madrone, ash, chinquapin, and alder; undergrowth, poison oak, hazel, fern, Oregon grape, arrowwood, blackberry, salmonberry, thimbleberry, vine maple, hawthorne, and young timber.</p>
	<p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>N. 88° 31' W., bet. secs. 26 and 35.</p> <p>Descend 185 ft. over broken NW. slope, through heavy timber and dense undergrowth.</p>
3.70	Ravine, drains N. 35° W.; asc. 5 ft- over NE. slope.
4.15	Spur, slopes N.; desc. 100 ft. over NW. slope.
7.00	Ravine, drains S. 70° W.; desc. 500 ft. over broken SW. slope.
33.80	North Fork Big Tom Folley Creek, 20 lks. wide, course S. 10° W.; asc. 195 ft. over NE. slope.
39.14	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 200px;"> <p>T 21 S R 7 W <i>FND OK 9/92</i> 1/4 S 26 <i>L. ROBERTS M115-63</i> S 35 1981</p> </div>
	<p>from which</p> <p style="margin-left: 40px;">A fir, 22 ins. diam., bears N. 51 1/4° E., 48 lks. dist., mkd. 1/4 S26 BT.</p> <p style="margin-left: 40px;">A fir, 29 ins. diam., bears S. 35° E., 64 1/2 lks. dist., mkd. 1/4 S35 BT.</p> <p>Ascend 295 ft. over NE. slope.</p>
49.25	Ravine, drains N. 65° E.; asc. 270 ft. over SE. slope.
56.85	Spur, slopes S.; desc. 175 ft. over SW. slope.
58.70	Dirt road, 20 lks. wide, bears N. 25° W. and S. 25° E.
69.15	Spur, slopes S. 25° W.; desc. 175 ft. over SW. slope.
78.00	Ravine, drains S. 20° W.; asc. 5 ft. over SE. slope.
78.28	The cor. of secs. 26, 27, 34, and 35, perpetuated and recorded by James W. Byron, Deputy Douglas County Surveyor, in 1957, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.