

County Surveyor's Record, Douglas County, Oregon

17240

Mineral Survey No. 997

FEET

dist., monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. above ground, firmly set, with standard BLM brass cap properly stamped.

A fir, 24 ins. diam., bears S. 87° E., 35.0 ft. dist., mkd. DMS 1 997 BT.

A cedar, 16 ins. diam., bears S. 15 3/4° W., 24.4 ft. dist., mkd. DMS 1 997 BT.

Thence S. 87°03' E.

1.00

Point for a witness cor. to Cor. No. 1. .

Set an iron post, 1 1/2 ins. diam., 30 ins. long, 24 ins. in the ground, with a brass disk, 2 ins. diam., mkd. DMS 1 997 WC.

600.00

Cor. No. 2.

Set an iron post, 1 1/2 ins. diam., 30 ins. long, 24 ins. in the ground and in a mound of stone, with a brass disk, 2 ins. diam., mkd. DMS 2 997; from which

A fir, 8 ins. diam., bears N. 16° E., 11.4 ft. dist., mkd. DMS 2 997 BT.

A fir, 6 ins. diam., bears S. 48° W., 10.9 ft. dist., mkd. DMS 2 997 BT.

Thence S. 02°58' W.

363.00

Cor. No. 3.

Set an iron post, 1 1/2 ins. diam., 30 ins. long, 24 ins. in the ground and in a mound of stone, with a brass disk, 2 ins. diam., mkd. DMS 3 997; from which

A fir, 6 ins. diam., bears S. 30° W., 18.5 ft. dist., mkd. DMS 3 997 BT.

A cedar, 10 ins. diam., bears N. 70° E. 32.2 ft. dist., mkd. DMS 3 997 BT.

Thence N. 87°03' W.

600.00

Cor. No. 4.

Set an iron post, 1 1/2 ins. diam., 30 ins. long, 20 ins. in the ground and in a mound of stone, with a brass disk, 2 ins. diam., mkd. DMS 4 997; from which

The 1/4 sec. cor. of secs. 5 and 6, perpetuated and recorded by the Douglas County Surveyor's Office, in 1970, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground and in a mound of stone, with brass cap mkd. COUNTY SURVEYORS OFFICE 1/4 S 6+5 T33S R4W 1970, bears S. 02°58' W., 1320.1 ft. dist.