

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

17244

CHAINS

from which the remains of the original bearing trees

A fir stump, 32 ins. diam., bears N. 48 1/2° E.,
42 1/2 lks. dist., with fragmentary scribe marks
visible on an open blaze.

A fir stump, 36 ins. diam., bears N. 63° W.,
24 lks. dist., with fragmentary scribe marks
visible on an open blaze.

and bearing trees mkd. by LaFlamme

A fir, 16 1/2 ins. diam., bears N. 50° E., 92 lks.
dist., with fragmentary scribe marks visible
on an open blaze.

A tan oak, 16 ins. diam., bears N. 29° W., 97 lks.
dist., with scribe marks 1/4 S17 BT visible
on an open blaze.

N. 0° 02' E., bet. secs. 16 and 17, blazing and marking
true line.

Descend 399 ft. over NE. slope, through moderate timber
and dense undergrowth.

17.88 Creek, 8 lks. wide, drains N. 48° E.; desc. 5 ft. over
broken N. slope.

18.20 Creek, 12 lks. wide, drains N. 45° E.; desc. 25 ft. over
NE. slope.

19.70 Dirt road, 15 lks. wide, bears N. 45° E. and S. 50° W.

20.09 Point for the N 1/16 sec. cor. of secs. 16 and 17.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam.,
18 ins. in the ground, and in mound of stone, 2 1/2 ft.
base, to top, with aluminum cap mkd.

T 30 S R 9 W
 N 1/16
 S 17 | S 16
 1982

from which

A fir, 21 ins. diam., bears N. 65° E., 40 lks.
dist., mkd. N 1/16 S16 BT.

A fir, 9 ins. diam., bears S. 40° W., 46 lks.
dist., mkd. N 1/16 S17 BT.

From this point, a steel fence post, firmly set,
projecting 3 ft. above ground, bears N. 18° E., 2 lks.
dist., from which

A fir, 7 ins. diam., bears S. 16° W., 77 lks.
dist., with 2 hacks visible.

Descend 13 ft. over NE. slope.

20.68 Creek, 30 lks. wide, course N. 30° W.; desc. 49 ft. over
NW. slope.

25.00 Left bank of the Middle Fork Coquille River, bears
N. 60° E., and S. 60° W., course S. 60° W.; thence across
river.