

County Surveyor's Record, Douglas County, Oregon

17247

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A fir snag, 32 ins. diam., bears N. 48 1/4° W.,
30 1/2 lks. dist., with a healed blaze.

and bearing trees mkd. by Jelley in 1962

A cedar, 15 ins. diam., bears N. 27 1/2° E., 35 lks.
dist., with a healed blaze.

A cedar, 13 ins. diam., bears S. 38° E., 239 lks.
dist., with scribe marks T30S R9W S17 BT visible
on an open blaze.

A fir, 15 ins. diam., bears S. 57° W., 121 lks.
dist., with a healed blaze.

A fir, 34 ins. diam., bears N. 71° W., 87 lks.
dist., with a healed blaze.

and new bearing trees

A live oak, 4 ins. diam., bears S. 89° E., 32 lks.
dist., mkd. X BT.

A fir, 7 ins. diam., bears S. 5° W., 51 lks.
dist., mkd. X BT.

From the cor. of secs. 8, 9, 16, and 17.

N. 89° 58' W., between secs. 8 and 17.

Ascend 120 ft. over broken SE. slope, through moderate
timber and undergrowth.

40.51

Point for the 1/4 sec. cor. of secs. 8 and 17, at propor-
tionate dist.; there is no remaining evidence of the
original cor.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam.,
24 ins. in the ground, with aluminum cap mkd.

T 30 S R 9 W
1/4 $\frac{S 8}{S 17}$
1982

from which

A fir, 10 ins. diam., bears N. 9° E., 5 lks.
dist., mkd. 1/4 S8 BT.

A cedar, 11 ins. diam., bears S. 66 1/2° E., 13 1/2 lks.
dist., mkd. 1/4 S17 BT.

Ascend 224 ft. over broken SE. slope.

81.02

The cor. of secs. 7, 8, 17, and 18.

Subdivision of Section 17,
T. 30 S., R. 9 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 17 and 20, perpetuated and
recorded by Vernon Tracy, Deputy Douglas County Surveyor,
in 1964, monumented with an iron post, 1 in. diam.,
firmly set, projecting 10 ins. above ground, with brass
cap mkd.