

# County Surveyor's Record, Douglas County, Oregon

17248

Subdivision of Sec. 17,  
T. 30 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 30 S  
1/4  $\frac{S\ 17}{S\ 20}$   
R 9 W  
1964

from which the remaining original bearing tree

A white fir, 25 ins. diam., bears N. 58° E., 13 lks. dist., with healed blaze.

and a bearing tree mkd. by Tracy

A fir stump, 11 ins. diam., bears S. 24° W., 75 lks. dist., with scribe marks 1/4 S20 BT visible on open blaze.

and a new bearing tree

A cedar, 17 ins. diam., bears S. 44° E., 90 lks. dist., mkd. 1/4 S20 BT.

N. 0° 27' W., on the N. and S. center line of sec. 17, marking and blazing the true line.

Descend 606 ft. over NW. slope, through moderate timber and dense undergrowth.

40.24

Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 30 S R 9 W  
C 1/4 S 17  
1982

from which

A fir, 9 ins. diam., bears S. 59° W., 21 lks. dist., mkd. C 1/4 S17 BT.

A fir, 8 ins. diam., bears N. 54° W., 24 lks. dist., mkd. C 1/4 S17 BT.

Descend 358 ft. over broken NW. slope.

46.10

Graveled road, 35 lks. wide, bears N. 76° E. and S. 76° W.

50.40

Graveled road, 30 lks. wide, bears N. 80° W. and S. 80° E.

57.60

Graveled road, 35 lks. wide, bears N. 75° W. and S. 75° E.

60.36

Point for the center N 1/16 sec. cor. of sec. 17.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, in mound of stone, 2 ft. base, to top, with aluminum cap mkd.