

# County Surveyor's Record, Douglas County, Oregon


Dependent Resurvey of a Portion of the South Boundary,  
T. 29 S., R. 6 W., Willamette Meridian, Oregon

17254

**CHAINS**

(Restoring the survey by Nathaniel Ford, U.S. Deputy Surveyor, in 1854, the retracement by Fred Mensch, U.S. Deputy Surveyor, in 1905, and the dependent resurvey by Hans W. Thielson and C. Albert White, Cadastral Surveyors, in 1958-59)

Beginning at the cor. of secs. 5 and 6 only, T. 30 S., R. 6 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.



from which the remains of the bearing trees mkd. by Mensch

A root hole, bears S. 43° W., 29 lks. dist., with a down fir, 34 ins. diam., alongside, with healed blaze.

and bearing trees mkd. by Thielsen and White

A fir snag, 18 ins. diam., bears S. 43 3/4° E., 102 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A fir, 28 ins. diam., bears S. 23° W., 95 lks. dist., with healed blaze.

and a bearing tree of no record

A fir, 48 ins. diam., bears N. 53° W., 12 lks. dist., with healed blaze.

and a bearing tree mkd. by Jelley and Rogers

A grand fir, 12 ins. diam., bears S. 78 1/2° E., 56 lks. dist., with scribe marks T30S R6W S5 BT visible on open blaze.

N. 89° 45' W., on the S. bdy. of sec. 31, marking and blazing the true line.

Descend 80 ft. over SW. slope.

17.60 Bottom of descent, drains S. 30° W.; asc. 40 ft. over SE. slope.

19.65 Dirt road, 20 lks. wide, bears N. 60° E. and S. 60° W.

20.42 A point established by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1977, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with aluminum cap, 1 1/2 ins. diam mkd. 1/16 WC 50 S 6 ONLY

from which bearing trees mkd. by Johnstone

A fir, 13 ins. diam., bears S. 26° W., 79 lks. dist., with scribe marks 1/16 WC visible on partially healed blaze.