

# County Surveyor's Record, Douglas County, Oregon

**17255** Dependent Resurvey, Portion of South Boundary,  
T. 29 S., R. 6 W., Willamette Meridian, Oregon

CHAINS									
	<p style="margin-left: 40px;">A yew, 10 ins. diam., bears S. 87° W., 46 1/2 lks. dist., with scribe marks 1/16 WC BT visible on open blaze.</p>								
25.25	<p style="margin-left: 40px;">Spur, slopes S. 40° W.; desc. 45 ft. over SW. slope.</p>								
27.65	<p style="margin-left: 40px;">Ravine, drains S. 20° W.; asc. 5 ft. over SE. slope.</p>								
28.29	<p style="margin-left: 40px;">Point for the 1/4 sec. cor. of sec. 31 only, hereinafter described.</p> <p style="margin-left: 40px;">Ascend 20 ft. over SE. slope.</p>								
34.15	<p style="margin-left: 40px;">Spur, slopes South; desc. 35 ft. over SW. slope.</p>								
37.35	<p style="margin-left: 40px;">Gravelled road, 20 lks. wide, bears N. 55° W. and S. 55° E.</p>								
39.33	<p style="margin-left: 40px;">The 1/4 sec. cor. of sec. 6 only, T. 30 S., R. 6 W., perpetuated and recorded by John H. Markam, Deputy County Surveyor, in 1956, monumented with an axle, 1 1/4 ins. diam., firmly set, projecting 20 ins. above the ground, from which the remains of the original bearing tree</p> <p style="margin-left: 80px;">A cedar, 53 ins. diam., bears N. 20° W., 26 lks. dist., with scribe marks 1/4 S31 BT visible on opened blaze. This tree was rescribed by Mensch in 1905.</p> <p style="margin-left: 40px;">and bearing trees mkd. by Markam</p> <p style="margin-left: 80px;">A grand fir, 30 ins. diam., bears N. 51° E., 38 lks. dist., with illegible scribe marks visible on partially healed double blaze.</p> <p style="margin-left: 80px;">A grand fir, 19 ins. diam., bears S. 85° W., 53 lks. dist., with healed double blaze.</p> <p style="margin-left: 40px;">At the corner point</p> <p style="margin-left: 40px;">Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="margin-left: 80px; text-align: center;"> <table style="border: none; margin: 0 auto;"> <tr> <td style="padding: 0 10px;">T 29 S</td> <td style="padding: 0 10px;">R 6 W</td> </tr> <tr> <td style="padding: 0 10px;">1/4</td> <td style="padding: 0 10px;">S 6</td> </tr> <tr> <td style="padding: 0 10px;">T 30 S</td> <td style="padding: 0 10px;">R 6 W</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1980</td> </tr> </table> </div> <p style="margin-left: 40px;">and a new bearing tree</p> <p style="margin-left: 80px;">A grand fir, 17 ins. diam., bears S. 68° E., 68 lks. dist., mkd. 1/4 S6 BT.</p> <p style="margin-left: 40px;">Deposit the axle alongside the iron post.</p> <hr style="width: 20%; margin-left: 40px;"/> <p style="margin-left: 40px;">N. 88° 47' W., beginning new measurement.</p> <p style="margin-left: 40px;">Descend 20 ft. over SW. slope.</p>	T 29 S	R 6 W	1/4	S 6	T 30 S	R 6 W	1980	
T 29 S	R 6 W								
1/4	S 6								
T 30 S	R 6 W								
1980									
2.80	<p style="margin-left: 40px;">Bottom of descent, drains S. 30° W.; asc. 5 ft. over SE. slope.</p>								
3.50	<p style="margin-left: 40px;">Top of ascent, slopes S.; desc. 30 ft. over SW. slope.</p>								
7.80	<p style="margin-left: 40px;">Bottom of descent, drains S.; asc. 10 ft. over SE. slope.</p>								
9.05	<p style="margin-left: 40px;">Point for the W 1/16 sec. cor. of sec. 31 only, hereinafter described.</p>								