

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of South Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon

17256

CHAINS

- Ascend 5 ft. over SE. slope.
- 12.50 Top of ascent, slopes S.; desc. 75 ft. over SW. slope.
- 22.35 Bottom of descent, drains S. 10° E.; asc. 15 ft. over SE. slope.
- 25.35 Spur, slopes S. 50° W.; desc. 290 ft. over NW. slope.
- 38.30 Ravine, drains S. 40° W.; asc. 5 ft. over SE. slope.
- 39.06 The cor. of Tps. 29 and 30 S., Rs. 6 and 7 W., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

T 29 S
R 7 W R 6 W
S 36 | S 31
S 1 | S 6
T 30 S
1968

from which the bearing trees mkd. by Mensch

A white oak, 28 ins. diam., bears N. 81 1/2° E.,
22 lks. dist., with healed blaze.

A white oak, 22 ins. diam., bears S. 20 1/2° E.,
50 lks. dist., with illegible scribe marks
visible on opened blaze.

and bearing trees mkd. by J. H. Markam, Registered
Engineer, No. 2880, in 1956

A madrone, 32 ins. diam., bears N. 3° E.,
80 1/2 lks. dist., with scribe mark 2 visible
on partially healed blaze.

A white oak, 16 ins. diam., bears S. 31 1/4° E.,
48 1/2 lks. dist., with healed blaze.

A white oak, 27 ins. diam., bears N. 50° W.,
267 lks. dist., with illegible scribe marks
visible on partially healed blaze.

and a bearing tree mkd. by Roseberry

A fir, 8 ins. diam., bears S. 49° W., 18 1/2 lks.
dist. with healed blaze.

From this point, an iron post, set by James W. Byron,
Deputy County Surveyor, in 1962, 1 in. diam., firmly set,
projecting 12 ins. above the ground, with brass cap
marked COUNTY SURVEYORS OFFICE T29S R6W R7W S36 S31 S1 S6
T30S 1962, bears S. 23 1/2° E., 0.025 chs. dist.

Land, mountainous.

Soil, rocky clay.

Timber, fir, yew, oak, madrone, hemlock, pine, alder,
cedar, chinquapin, maple, and willow; undergrowth, poison
oak, ferns, blackberry, huckleberry, wild rose, arrow-
wood, hazel, salmonberry, Oregon grape, salal, and young
timber.