

County Surveyor's Record, Douglas County, Oregon

17257

Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Nathaniel Ford, U.S. Deputy Surveyor, in 1854, the retracement by Fred Mensch, U.S. Deputy Surveyor, in 1905, the retracement by Roy T. Campbell, U.S. Deputy Surveyor, in 1910, and the dependent resurvey by Lynn M. Roseberry, Cadastral Surveyor, in 1968)

From the cor. of Tps. 29 and 30 S., Rs. 6 and 7 W.


N. 2° 32' E., bet. secs. 31 and 36.

Ascend 205 ft. over SE. slope, through heavy timber and dense undergrowth.

10.80 Dirt road, 15 lks. wide, bears N. 10° E. and S. 15° W.

13.00 Dirt road, 15 lks. wide, bears N. 80° E. and S. 70° W.

19.34 The S 1/16 sec. cor. of sec. 31 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.



from which bearing trees mkd. by Roseberry

An oak, 15 ins. diam., bears N. 44° E., 220 1/2 lks. dist., with healed blaze.


A fir, 20 ins. diam., bears S. 79° E., 297 lks. dist., with healed blaze. (Record, S. 76° E.)

N. 2° 38' E., beginning new measurement.

Ascend 85 ft. over SE. slope.

8.50 Ridge, bears N. 85° E. and S. 40° W.; desc. 255 ft. over broken NW. slope.

19.38 The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.



from which bearing trees mkd. by Mensch

A decayed fir stump, size indeterminate, bears S. 88° E., 27 lks. dist., no marks visible.

A sawed fir stump, 28 ins. diam., bears S. 68° W., 18 lks. dist., with scribe marks 1/4 S36 visible on opened blaze.

and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1959