

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of West Boundary,  
T. 29 S., R. 6 W., Willamette Meridian, Oregon

17258

**CHAINS**

A root hole, bears S. 11° E., 7 1/2 lks. dist., with a down fir, 20 ins. diam., alongside, with fragmentary scribe marks visible on partially healed double blaze.

A grand fir, 15 ins. diam., bears N. 57 3/4° W., 67 lks. dist., with healed double blaze.

and a bearing tree mkd. by Roseberry

A yew, 8 ins. diam., bears N. 80 3/4° E., 83 1/2 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, willow, oak, madrone, maple, chinquapin, fir, cedar, yew, pine, hemlock, and alder; undergrowth, poison oak, ferns, blackberry, hazel, arrowwood, huckleberry, Oregon grape, salal, wild rose, salmonberry, and young timber.

Dependent Resurvey of  
a Portion of the Subdivisional Lines,  
T. 29 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the survey  
by Fred Mensch, U.S. Deputy Surveyor, in 1905)

From the 1/4 sec. cor. of secs. 31 and 32, perpetuated and recorded by John H. Markam, Deputy County Surveyor, in 1957, from which the remains of the original bearing tree

A fir, 15 ins. diam., bears N. 28° E., 39 lks. dist., with healed blaze.


and bearing trees mkd. by Markam

A cedar, 14 ins. diam., bears N. 10° E., 81 lks. dist., with healed blaze.

A sawed fir stump, 18 ins. diam., bears S. 46° E., 57 lks. dist., with illegible scribe marks visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which a new bearing tree

A fir, 4 ins. diam., bears N. 79 1/2° W., 35 lks. dist., mkd. X BT.

S. 0° 51' W., bet. secs. 31 and 32, marking and blazing the true line.