

# County Surveyor's Record, Douglas County, Oregon

**17259**

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 6 W., Willamette Meridian, Oregon

**CHAINS**


Ascend 735 ft. over broken NW. slope, through heavy timber and dense undergrowth.

20.45 Ridge, bears N. 75° E. and S. 75° W.; desc. 365 ft. over SE. slope.

21.00 Gravelled road, 20 lks. wide, bears E. and W., also enter along timber cut line, edge bears S. and W.

36.70 Gravelled road, 20 lks. wide, bears N. 75° E. and S. 75° W.

39.30 The original closing cor. of secs. 31 and 32, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.



form which the remains of the original bearing trees

A fir, 18 ins. diam., bears N. 61 1/2° E., 45 lks. dist., with healed blaze.

and bearing trees mkd. by John H. Markam, Deputy County Surveyor, in 1956

A yew, 23 ins. diam., bears N. 51 1/2° E., 67 1/2 lks. dist., with scribe marks S32 T29S R6W BT visible on open blaze.

A cedar, 18 ins. diam., bears S. 5 1/2° W., 48 lks. dist., with healed double blaze.

and bearing trees mkd. by Thielsen and White


A grand fir, 25 ins. diam., bears N. 79° E., 61 lks. dist., with healed blaze.

A fir, 50 ins. diam., bears N. 53 1/2° W., 78 lks. dist., with scribe marks T29S R6W S31 BT visible on bark.

Add the marks AM to the brass cap.

39.65 Point for the closing corner of secs. 31 and 32, at intersection with the S. bdy. of the Tp.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



*Sec H. Johnstone  
Report  
6/23/104  
C.S. 11/23/190*

from which new bearing trees