

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **17260**
T. 29 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A fir, 8 ins. diam., bears N. 64 1/4° E., 54 lks.
dist., mkd. T29S R6W S32 CC BT.

A fir, 6 ins. diam., bears N. 72 3/4° W., 88 1/2 lks.
dist., mkd. T29S R6W S31 CC BT.

From this point, the cor. of secs. 5 and 6 only,
T. 30 S., R. 6 W., bears N. 87° 59' W., 11.89 chs. dist.,
hereinbefore described.

From this same point, the 1/4 sec. cor. of sec. 5 only,
T. 30 S., R. 6 W., bears S. 87° 59' E., 27.29 chs. dist.,
monumented with an iron post, 2 1/2 ins. diam., firmly set,
projecting 6 ins. above ground, with brass cap mkd.

1/4	S 5
T 30 S	R 6 W
1958	

from which bearing trees mkd. by Thielsen and White

A cedar snag, 18 ins. diam., bears S. 51 1/2° E.,
50 lks. dist., with scribe marks 1/4 S5 BT
visible on open blaze.

A fir, 16 ins. diam., bears S. 31° W.,
37 lks. dist., with healed blaze.

and a bearing tree mkd. by Jelley

A fir, 6 ins. diam., bears S. 7 3/4° E., 154 lks.
dist., with scribe marks 1/4 S5 BT visible on
open blaze.

Land, mountainous.
Soil, rocky clay.

Timber, alder, maple, yew, pine, hemlock, fir, oak,
madrone, cedar, and chinquapin; undergrowth, poison oak,
hazel, ferns, huckleberry, salmonberry, arrowwood, Oregon
grape, salal, and young timber.

The point for the 1/4 sec. cor. of sec. 31 only, at propor-
tionate distance on the S. bdy. of sec. 31.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 29 S	R 6 W
1/4 S 31	
T 30 S	R 6 W
1980	

from which

A fir, 5 ins. diam., bears N. 55 1/4° E.,
97 lks. dist., mkd. 1/4 S31 BT.

A grand fir, 11 ins. diam., bears N. 23 1/2° W.,
122 lks. dist., mkd. 1/4 S31 BT.