

# County Surveyor's Record, Douglas County, Oregon

17261

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 6 W., Willamette Meridian, Oregon

**CHAINS**

From this point, the 1/4 sec. cor. of sec. 6 only,  
T. 30 S., R. 6 W., bears N. 89° 45' W., 11.04 chs. dist.,  
hereinbefore described.

The point for the W 1/16 sec. cor. of sec. 31 only, at  
proportionate distance on the S. bdy. of sec. 31.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in  
the ground, with brass cap mkd.

W 1/16    S 31

1980

from which

A fir, 16 ins. diam., bears North, 3 1/2 lks.  
dist., mkd. W 1/16 S31 BT.

A fir, 10 ins. diam., bears N. 60° E., 19 lks.  
dist., mkd. W 1/16 S31 BT.

From this point, the 1/4 sec. cor. of sec. 6 only,  
T. 30 S., R. 6 W., bears S. 88° 47' E., 9.05 chs. dist.,  
hereinbefore described.

From the cor. of secs. 29, 30, 31, and 32, perpetuated  
and recorded by John H. Markam, Jr., Registered Logging  
Engineer, No. 2880, in 1956, monumented with an iron  
pipe, 1 in. diam., firmly set, projecting 6 ins. above  
ground, alongside of which is the original basalt stone,  
15 x 12 x 8 ins., firmly set, projecting 6 ins. above  
ground, with 5 notches on E. and 1 notch on S. edges,  
from which the remains of the original bearing trees

A fir snag, 23 ins. diam., bears N. 72° E., 27 lks.  
dist., with healed blaze.

A fir snag, 21 ins. diam., bears S. 42° E., 7 lks.  
dist., with healed blaze.

A fir snag, 15 ins. diam., bears S. 86° W., 11 lks.  
dist., with illegible scribe marks visible on  
opened blaze.

and bearing trees mkd. by Markam

A madrone, 25 ins. diam., bears S. 12° W.,  
36 lks. dist., with scribe marks S31 T29S R6W  
visible on bark.

A madrone snag, 20 ins. diam., bears N. 23° W.,  
53 lks. dist., with scribe marks S30 T29S R6W 2880  
visible on bark.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with brass cap mkd.

T 29 S    R 6 W

S 30 | S 29  
S 31 | S 32

1980