

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 6 W., Willamette Meridian, Oregon

17262

CHAINS

from which new bearing trees

A fir, 13 ins. diam., bears N. 20 1/2° E., 29 lks. dist., mkd. T29S R6W S29 BT.

A cedar, 7 ins. diam., bears S. 69° E., 39 lks. dist., mkd. T29S R6W S32 BT.

A cedar, 15 ins. diam., bears S. 29° W., 15 lks. dist., mkd. T29S R6W S31 BT.

A cedar, 16 ins. diam., bears N. 73 1/2° W., 24 1/2 lks. dist., mkd. T29S R6W S30 BT.

Deposit the stone and the iron pipe alongside the iron post.

N. 89° 25' W., bet. secs. 30 and 31.

Descend 25 ft. over SW. slope, through dense undergrowth and heavy timber.

2.10 Creek, 2 lks. wide, course S. 70° W.; desc. 190 ft. over SW. slope.

11.40 Creek, 6 lks. wide, course N. 30° W.; asc. 25 ft. over NE. slope.

13.30 Spur, slopes N. 50° W.; desc. 30 ft. over SW. slope.

14.80 Creek, 5 lks. wide, course N. 20° W.; asc. 15 ft. over NE. slope.

15.15 Spur, slopes N. 20° W.; desc. 10 ft. over NW. slope.

15.75 Creek, 1 lk. wide, course N. 5° E.; asc. 5 ft. over NE. slope.

16.05 Creek, 1 lk. wide, course N. 60° E.; asc. 20 ft. over NE. slope.

20.01 Point for the E 1/16 sec. cor. of secs. 30 and 31.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 30}{S\ 31}$

1980

from which

A fir, 15 ins. diam., bears S. 55° E., 23 1/2 lks. dist., mkd. E 1/16 S31 BT.

A triple yew, 11 ins. diam., bears N. 20 1/2° W., 48 lks. dist., mkd. E 1/16 S30 BT.

Ascend 20 ft. over NE. slope.

20.75 Spur, slopes N. 20° E.; desc. 35 ft. over NW. slope.

22.00 Gravelled road, 20 lks. wide, bears N. 35° E. and S. 35° W.

23.25 Barrett Creek, 5 lks. wide, course N. 40° E.; asc. 170 ft. over NE. slope.