

County Surveyor's Record, Douglas County, Oregon

17263 Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
31.80	Spur, slopes N. 35° E.; desc. 215 ft. over W. slope.
40.02	The 1/4 sec. cor. of secs. 30 and 31, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with the original diorite stone, 12 x 10 x 8 ins., mkd. 1/4 on N. face, alongside, with brass cap mkd.
	<p>COUNTY SURVEYORS OFFICE</p> <p>T 29 S R 6 W</p> <p> 1/4 $\frac{S\ 30}{S\ 31}$</p> <p> 1962</p>
	from which the remains of the original bearing trees
	A fir snag, 24 ins. diam., bears S. 20° W., 32 lks. dist., with illegible scribe marks visible on opened blaze.
	A cedar root crown, bears N. 1° W., 7 lks. dist., with down cedar, 50 ins. diam., alongside, no marks visible.
	and bearing trees mkd. by Byron
	A madrone, 18 ins. diam., bears N. 24 1/2° E., 153 lks. dist., with healed blaze.
	A madrone, 15 ins. diam., bears S. 18° E., 48 lks. dist., with healed blaze.

	S. 89° 50' W., beginning new measurement.
	Descend 70 ft. over W. slope.
1.45	Creek, 5 lks. wide, course N. 15° W.; asc. 25 ft. over SW. slope.
8.55	Spur, slopes N. 20° W.; desc. 25 ft. over NW. slope.
10.80	Dry creek bed, 5 lks. wide, course N.; asc. 5 ft. over SW. slope.
11.00	Spur, slopes N. 10° W.; desc. 105 ft. over NW. slope.
14.25	Dry creek bed, 5 lks. wide, course N. 40° E.; asc. 30 ft. over SW. slope.
18.00	Spur, slopes N. 15° E.; desc. 5 ft. over NW. slope.
20.33	Point for the W 1/16 sec. cor. of secs. 30 and 31.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>W 1/16 $\frac{S\ 30}{S\ 31}$</p> <p> 1980</p>
	from which