

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 6 W., Willamette Meridian, Oregon

17264

CHAINS

A fir, 9 ins. diam., bears N. 66 1/2° E., 75 lks.  
dist., mkd. W 1/16 S30 BT.

A fir, 6 ins. diam., bears S. 25 1/2° E., 19 lks.  
dist., mkd. W 1/16 S31 BT.

Descend 5 ft. over NW. slope.

20.40 Dry Creek bed, 4 lks. wide, course N. 40° E.; asc. 30 ft.  
over SW. slope.

21.45 Spur, slopes N. 50° E.; desc. 30 ft. over NW. slope.

23.15 Creek, 3 lks. wide, course N. 50° E.; asc. 460 ft. over  
NE. slope.

44.30 Spur, slopes N. 10° E.; desc. 5 ft. over NW. slope.

47.22 The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the  
Tp., perpetuated and recorded by Arthur Boyer, Registered  
Civil Engineer, No. 1581, in 1952, and further per-  
petuated and recorded by James W. Byron, Registered Land  
Surveyor, No. 303, in 1959, monumented with an iron post,  
1 1/4 ins. diam., firmly set, projecting 12 ins. above  
ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 29 S			
R	S 25	S 30	R
7		6	6
W	S 36	S 31	W

1959

from which the remains of the bearing trees mkd. by  
Mensch

A root hole, bears N. 33° E., 36 lks. dist.,  
with a down madrone, 10 ins. diam., alongside,  
no marks visible.

and bearing trees mkd. by Boyer

A fir snag, 25 ins. diam., bears East, 29 lks.  
dist., with scribe marks S30 T29S R6W S BT  
visible on bark.

A fir, 23 ins. diam., bears S. 56° E., 109 lks.  
dist., with scribe marks S31 T29S R6W BT  
visible on bark.

and new bearing trees

A fir, 8 ins. diam., bears N. 79° E., 48 1/2 lks.  
dist., mkd. T29S R6W S30 BT.

A fir, 8 ins. diam., bears S. 27° W., 37 lks.  
dist., mkd. T29S R7W S36 BT.

A fir, 8 ins. diam., bears N. 63° W., 58 lks.  
dist., mkd. T29S R7W S25 BT.

The corner is located in a fence corner, extending N. and  
W.