

County Surveyor's Record, Douglas County, Oregon

17265

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.
Soil, rocky clay.
Timber, pine, cedar, yew, ash, maple, oak, fir, hemlock, alder, and willow; undergrowth, poison oak, vine maple, ferns, arrowwood, hazel, Oregon grape, salal, huckleberry, salmonberry, thimbleberry, blackberry, wild rose, and young timber.

Subdivision of Section 31,
T. 29 S., R. 6 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of sec. 31 only, on the S. bdy. of the Tp.


N. 0° 27' E., on the N. and S. center line of sec. 31.

Ascend 305 ft. over SE. slope, through heavy timber and dense undergrowth.

14.90 Ridge, bears N. 85° E. and N. 75° W.; desc. 140 ft. over NW. slope.

19.61 Point for the center S 1/16 sec. cor. of sec. 31.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 3 ins. diam., bears N. 9° E., 50 1/2 lks. dist., mkd. X BT.

A fir, 4 ins. diam., bears S. 35 3/4° E., 51 lks. dist., mkd. X BT.


Descend 260 ft. over NW. slope.

28.05 Ravine, drains N. 30° E.; desc. 245 ft. over broken NE. slope.

32.20 Gravelled road, 30 lks. wide, bears N. 35° W. and S. 35° E.

39.30 Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 7 ins. diam., bears S. 30 1/4° E., 35 1/2 lks. dist., mkd. C 1/4 S31 BT.