

# County Surveyor's Record, Douglas County, Oregon

17266

Subdivision of Section 31,  
T. 29 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 5 ins. diam., bears N. 27 1/2° W., 28 1/2 lks. dist., mkd. C 1/4 S31 BT.</p> <p>Descend 120 ft. over broken NE. slope.</p>
54.20	Spur, slopes N. 50° E.; desc. 50 ft. along spur top.
57.40	Gravelled road, 25 lks. wide, bears N. 10° E. and S. 30° W.
62.30	Spur, slopes N. 10° E.; desc. 445 ft. over NW. slope.
65.80	Slope changes to NE.
74.85	Dry creek bed, 3 lks. wide, course N. 10° W.; desc. 20 ft. along broken W. slope.
79.53	The 1/4 sec. cor. of secs. 30 and 31.
<p>From the 1/4 sec. cor. of secs. 31 and 32.</p> <p>N. 89° 44' W., on the E. and W. center line of sec. 31.</p> <p>Descend 170 ft. over broken NW. slope, through moderate timber and dense undergrowth.</p>	
9.90	Bottom of descent, drains N. 15° E.; asc. 20 ft. over NE. slope.
11.70	Spur, slopes N. 25° E.; desc. 45 ft. over NW. slope.
12.75	Gravelled road, 25 lks. wide, bears N. 30° E. and S. 30° W.
14.95	Creek, 5 lks. wide, course North; asc. 75 ft. over NE. slope.
19.95	Spur, slopes North; desc. 10 ft. over broken NW. slope.
20.23	Point for the center E 1/16 sec. cor. of sec. 31.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">C \frac{E \ 1/16}{S \ 31} C</math> <p>1980</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 23 1/4° E., 6 1/2 lks. dist., mkd. C-E 1/16 S31 BT.</p> <p style="padding-left: 40px;">A yew, 11 ins. diam., bears S. 64° W., 22 1/2 lks. dist., mkd. C-E 1/16 S31 BT.</p> <p>Descend 25 ft. over NW. slope.</p>
24.55	Head of ravine, drains North; asc. 40 ft. over NE. slope.
28.30	Spur, slopes N. 15° W.; desc. 85 ft. over SW. slope.
30.90	Ravine, drains N. 60° W.; asc. 80 ft. over NE. slope.
40.46	The center 1/4 sec. cor. of sec. 31.