

# County Surveyor's Record, Douglas County, Oregon.

17267

Subdivision of Section 31,  
T. 29 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	Ascend 55 ft. over NE. slope.
49.85	Spur, slopes N. 15° E.; desc. 75 ft. over broken NW. slope.
50.15	Gravelled road, 20 lks. wide, bears N. 10° E. and S. 10° W.
56.55	Ravine, drains N. 10° E.; asc. 20 ft. over NE. slope.
58.80	Spur, slopes North; desc. 30 ft. over broken NW. slope.
60.65	Point for the center W 1/16 sec. cor. of sec. 31.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	$C \frac{W \ 1/16}{S \ 31} C$ <p>1980</p>
	from which
	A fir, 13 ins. diam., bears S. 18 3/4° E., 33 lks. dist., mkd. C-W 1/16 S31 BT.
	A cedar, 7 ins. diam., bears N. 17° W., 44 1/2 lks. dist., mkd. C-W 1/16 S31 BT.
	Descend 55 ft. over broken NW. slope.
67.35	Creek, 1 lk. wide, course N. 25° E.; asc. 70 ft. over SE. slope.
69.40	Spur, slopes N. 45° E.; continue to ascend 20 ft. over NE. slope.
71.90	Spur, slopes N. 20° W.; desc. 60 ft. over NW. slope.
75.15	Ravine, drains N. 25° W.; asc. 80 ft. over NE. slope.
85.70	Dirt road, 20 lks. wide, bears N. and S.
86.30	Ridge, bears N. 10° E. and S. 10° W.; desc. 70 ft. over NW. slope.
89.08	The 1/4 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp.
	From the center E 1/16 sec. cor. of sec. 31.
	N. 0° 08' E., on the N. and S. center line of the NE 1/4 of sec. 31.
	Descend 290 ft. over broken NW. slope, through moderate timber and dense undergrowth.
10.75	Creek, 2 lks. wide, course N. 25° W.; desc. 135 ft. over broken NE. slope.
24.50	Bottom of descent, drains N. 45° W.; asc. 5 ft. over SW. slope.
29.50	Spur, slopes N. 15° W.; desc. 145 ft. over NE. slope.