

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 31,  
T. 29 S., R. 6 W., Willamette Meridian, Oregon

17268

CHAINS 40.12	The E 1/16 sec. cor. of secs. 30 and 31.
7.90	From the W 1/16 sec. cor. of sec. 31 only, on the S. bdy. of the tp.  N. 0° 20' E., on the N. and S. center line of the SW1/4 of sec. 31.  Ascend 270 ft. over SE. slope, through heavy timber and dense undergrowth.
10.05	Gravelled road, 25 lks. wide, bears E. and W.
16.75	Spur, slopes S. 65° W.; desc. 160 ft. over NW. slope.  Head of ravine, drains W.; asc. 5 ft. over SW. slope.
19.61	Point for the SW 1/16 sec. cor. of sec. 31, at intersection with the E. and W. center line of the SW 1/4 of sec. 31.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SW 1/16  S 31  1980
	from which  A fir, 5 ins. diam., bears N. 81° E., 16 lks. dist., mkd. SW 1/16 S31 BT.  A fir, 15 ins. diam., bears N. 65° W., 58 lks. dist., mkd. SW 1/16 S31 BT.  and bearing trees of no record  A fir, 18 ins. diam., bears S. 89 1/2° E., 74 lks. dist., with scribe marks 1/16 S S31 visible on opened double blaze.  A fir, 18 ins. diam., bears S. 63° W., 33 lks. dist., with illegible scribe marks visible on opened double blaze.
20.65	Ascend 5 ft. over SW. slope.  Ridge bears S. 65° E. and N. 65° W.; desc. 180 ft. over NW. slope.
29.65	Spur, slopes N. 30° W.; desc. 125 ft. over NE. slope.
32.60	Gravelled road, 25 lks. wide, bears N. 55° E. and S. 55° W.
35.45	Spur, slopes N. 40° E.; desc. 130 ft. over NW. slope.
39.17	The center W 1/16 sec. cor. of sec. 31.
	From the center S 1/16 sec. cor. of sec. 31.  N. 89° 20' W., on the E. and W. center line of the SW 1/4 of sec. 31.