

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 17274
T. 30 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	<div style="text-align: center;"> T 30 S R 9 W 1/4 S 5 S 4 1980 </div>
	from which A hemlock, 27 ins. diam., bears N. 57° E., 39 lks. dist., mkd. 1/4 S4 BT. A hemlock, 17 ins. diam., bears S. 74 1/2° W., 30 lks. dist., mkd. 1/4 S5 BT. Descend 85 ft. over NW. slope.
47.55	Bottom of descent, slopes W.; asc. 35 ft. over SW. slope.
51.60	Top of ascent, slopes W.; desc. 60 ft. over NW. slope.
53.95	Bottom of descent, slopes N. 70° W.; asc. 50 ft. over SW. slope.
58.75	Spur, slopes N. 70° W.; desc. 10 ft. over NW. slope.
60.435	Point for the N 1/16 sec. cor. of secs. 4 and 5. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> N 1/16 S 5 S 4 1980 </div>
	from which A hemlock, 20 ins. diam., bears S. 41 1/2° E., 60 lks. dist., mkd. N 1/16 S4 BT. A hemlock, 7 ins. diam., bears S. 30° W., 33 lks. dist., mkd. N 1/16 S5 BT. Descend 90 ft. over NW. slope.
63.10	Bottom of descent, slopes S. 70° W.; asc. 50 ft. over S. slope.
66.35	Top of ascent, slopes S. 70° W.; desc. 50 ft. over NW. slope.
68.30	Bottom of descent, slopes SW.; asc. 65 ft. over general S. slope.
78.80	The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1964, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	<div style="text-align: center;"> T 29 S R 9 W S 32 S 33 S 5 S 4 T 30 S 1964 </div>