

County Surveyor's Record, Douglas County, Oregon

T. 30 S., R. 8 W., Willamette Meridian, Oregon

17278

CHAINS

The following field notes are those of the dependent resurvey of a portion of the west boundary and subdivisional lines, and subdivision of section 19, Township 30 South, Range 8 West, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The west boundary of the township was surveyed by Dennis Hathorn in 1856.

The subdivisional lines were surveyed by William H. Byars in 1882.

A portion of the subdivisional lines was resurveyed by Charles E. Akin in 1972.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1021, Oregon, dated February 28, 1980.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original position. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines not forming a closure were measured twice.

The geographic position of the south 1/16 section corners of sections 19 and 20, as determined by a direct tie to United States Coast and Geodetic Survey triangulation station "LIVE OAK", is as follows:

Latitude 42° 56' 32.7" N. Longitude 123° 40' 51.1" W.

The mean magnetic declination is 20° 00' E.

Dependent Resurvey of a Portion of the West Boundary,
T. 30 S., R. 8 W., Willamette Meridian, Oregon

(Restoring the survey
by Dennis Hathorn, U.S. Deputy Surveyor, in 1856)

Beginning at the cor. of secs. 19, 24, 25, and 30, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1964, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
 R S 24 | S 19 R
 9 ——— | ——— 8
 W S 25 | S 30 W

1964